



SOLITEX® ADHERO

Full-surface self-adhesive airtightness and weathering-protection membrane

SOLITEX ADHERO allows airtightness to be achieved - for example, on mineral subsurfaces and wood-based products. At the same time, it provides protection against weathering to structures during the construction phase.



Advantages

- ✓ Protects the structure: Diffusion-permeable and maximum protection against driving rain
- ✓ Keeps building components dry by means of a pore-free moisture-active functional membrane
- ✓ Easy and reliable installation thanks to its split release film
- ✓ Sticks immediately to subsurfaces with sufficient load-bearing capacity
- ✓ Permanent protection thanks to the high resistance to ageing and heat of the TEEE membrane
- ✓ 3 months of outdoor exposure



www.proclima.com

... and the insulation
is perfect



SOLITEX® ADHERO

Technical data

Full-surface self-adhesive airtightness and weathering-protection membrane



Substance	
Protective and covering fleece	Polypropylene microfibre
Adhesive	special pressure sensitive acrylic adhesive
Membrane	monolithic TEEE
Release film	silicone-coated PE film, split 25/125 cm
Attribute	
Value	
Surface weight	240 ±5 g/m ²
Thickness	0.70 ±0.05 mm
s ₀ -value/humidity variable	0.40 ±0.08 m/0.25 - 0.8 m
Reaction to fire	E
Exposure time	3 months
Water column	10.000 mm
Water resistance non-aged/aged*	W1 / W1
Airtightness	passed
Tensile strength MD/CD / aged*	250 ±30 N/5 cm/200 ±30 N/5 cm / 190 ±20 N/5 cm/160 ±20 N/5 cm
*Artificial ageing by long term at 100°C; 212 °F	passed
Temperature resistance	permanent -40 °C to 100 °C; -40 °F to 212 °F
Roof lining membrane	UDB-A
Temporary roof covering; suitable as ...	yes

Forms of delivery

Art. no.	GTIN	Length	Width	Surface area	Weight	Sales unit	Container
1AR01513	4026639215130	30 m	1.50 m	45 m ²	12 kg	1	24

Application



1 The membranes are generally installed horizontally



2 Possible alternative: vertical installation



3 Sealing to rough subsurfaces using ORCON F



4 Form the sub-sill flashing using EXTONSEAL ENCORS



5 Seal the window joints on the inside and outside using CONTEGA



6 Pipe feed-through with ROFLEX/KAFLEX

Further information about application and construction is given in the pro clima planning documentation and application recommendations.

(Please also note the recommendations of the currently valid version of the pro clima application matrix.)

Information and ordering service:

Phone: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.de

Engineering Hotline:

Phone: +49 (0) 62 02 - 27 82.45
eMail: technik@proclima.de

MOLL
bauökologische Produkte GmbH
Rheinalstraße 35 - 43
D-68723 Schwetzingen
Phone: +49 (0) 62 02 - 27 82.0
eMail: info@proclima.com

www.proclima.com

